

UGELLI ASSIALI A CONO VUOTO - SERIE O4 AXIAL FEED HOLLOW-CONE NOZZLES - O4 SERIES

0



Tipo / Type O4 y



Tipo / Type O4 x

CARATTERISTICHE

- Ricavato da barra
- Diffusore a disco con fresature radiali inclinate
- Gocce di grandi dimensioni

APPLICAZIONI CONSIGLIATE

- Impianti di condizionamento e umidificazione
- Raffreddamento materiali
- Abbattimento polveri
- Raffreddamento e lavaggio aria e gas
- Trattamento con acqua demineralizzata
- Trattamenti chimici industriali
- Umidificazione di filtri
- Essiccamento per spruzzatura
- Raffreddamento di vapore

CHARACTERISTICS

- Made out of bar
- Swirl-disc with raking radial millings
- Big-sized droplets

TYPICAL APPLICATIONS

- Air conditioning and humidifying plants
- Materials cooling
- Dust suppression
- Cooling and cleaning of air and gas
- Treatment with demineralized water
- Chemical-industrial treatments
- Filter spraying
- Spray drying
- Desuperheating

CODE STD. MAT.


02 AISI 316
04 AISI 303
06 Ottone/Brass
07 Ottone nichelato cromato /Chromium-plated brass
08 PVC
10 Polipropilene/Polypropylene

CODE NOT STD. MAT.


9 Delrin
17 Hastelloy c
18 Titanio/Titanium
21 PVDF
22 Polizene
36 Teflon

DATI OPERATIVI - OPERATIVE DATA

TIPO / TYPE O4 x-y Dimensione raccordo Thread dimension			CODICE PORTATA FLOW CODE	PORTATA / FLOW l/min											AMPIEZZA ANGOLO DI SPRUZZO SPRAY ANGLE WIDTH		
1"1/4	1"1/2	2"		Ø E mm.	Ø U mm.	0,5 bar	1 bar	1,5 bar	2 bar	3 bar	4 bar	5 bar	7 bar	10 bar	60°	90°	120°
▼			416	12,0	14,0	20	28	34	39	48	55	62	73	87	●	●	●
▼			434	12,2	15,0	24	34	42	48	59	68	76	90	107	●	●	●
▼			459	12,4	15,5	30	42	51	59	72	83	93	110	132	●	●	●
▼			474	12,6	16,0	34	47	58	67	82	95	106	125	150	●	●	●
▼			496	12,8	16,4	39	55	68	78	96	110	123	146	174	●	●	●
	▼		532	13,0	17,0	48	68	83	96	118	136	152	180	215	●	●	●
	▼		558	13,4	17,3	54	76	94	108	132	153	171	202	241	●	●	●
	▼		584	13,6	18,0	61	86	105	121	148	171	191	226	271	●	●	●
	▼		616	14,0	18,4	68	96	118	136	167	192	215	254	304	●	●	●
		▼	628	14,3	19,8	74	105	128	148	181	209	234	277	331	●	●	●
		▼	641	14,5	20,2	81	114	139	161	197	228	255	301	360	●	●	●
		▼	665	15,0	20,8	93	131	160	185	227	262	293	346	414	●	●	●



Tipo / Type O4 y



Tipo / Type O4 x

DIMENSIONI DIMENSIONS	RACCORDO GAS CILINDRICO BSP BSP THREAD						RACCORDO MASCHIO GAS CONICO BSPT MALE BSPT THREAD		
	1"1/4		1"1/2		2"		1"1/4	1"1/2	2"
	x	y	x	y	x	y	y	y	y
A	65	50	70	55	100	80	50	55	80
B	19	19	19	19	20	20	19	19	20
CH/SW/Ø	50	45	55	50	Ø 70	60	45	50	Ø 65